SDS ATTACHMENT

PLEASE ATTACH THIS COMPLETED SHEET TO THE SDS FOR:

PRODUCT: SC-90

SDS DATE: 27 May 2021

1. Supplier:Tradegear LtdWebsite: www.tradegear.co.nzLevel 1, 99 Clarence StreetEmail: office@tradegear.co.nz

Level 1, 99 Clarence Street Riccarton, Christchurch 8011

New Zealand

Phone: 0800 22 44 34 or +64 3 341 8055 Fax: 0800 22 11 51 or +64 9 522 8833 24 hr emergency contact: +64 21 510 622

Emergency Information: National Poison Centre: 0800 764 766 (0800 POISON)

2 & 15. Hazards Identification & Regulatory Requirements:

Product Name: Product Use:	SC-90 Heavy duty cleaner (aerosol)
Group Standard, Approval Number	Aerosols (Subsidiary Hazard) Group Standard 2020 - HSR002519 All ingredients are listed on the New Zealand Inventory of Chemicals (NZIoC)
GHS Classification: [Note: classification based on the CRC Industries SDS]	Aerosols Category 3 Eye irritation Category 2
Hazard Statement and Precautions, including Class 9 statements where applicable: Warning	Pressurised container: May burst if heated. Causes serious eye irritation. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Wear eye protection/face protection. Protect from sunlight. Do not expose to temperatures exceeding 50°C.
Tolerable Exposure Limit or Environmental Exposure Limit:	None applied to this product or its ingredients.

SAFETY DATA SHEET

ACTION CAN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

SC-90

Registration number

None. **Synonyms**

BDS002570AE **Product code** Issue date 27-May-2021

Version number

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaners - Heavy duty

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company name CRC Industries UK Ltd.

Wylds Road **Address**

> Castlefield Industrial Estate TA6 4DD Bridgwater Somerset

United Kingdom +44 1278 727200

Telephone +44 1278 425644 Fax E-mail hse.uk@crcind.com Website www.crcind.com

1.4. Emergency telephone

number

Tel.:(+44)(0)1278 72 7200 (office hours)

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons

Information Centre

Belgium National Poisons

Control Center

Toxicological Information

Centre

available for the Emergency Service.) 070 245 245 (Available 24 hours a day. SDS/Product information may not be

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Bulgaria National

+359 2 9154233 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Czech Republic National Poisons Information

Centre

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons

Control Center

+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Estonia National Poisons Information Centre

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be

available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Hungary National Emergency Phone Number

36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Lithuania Neatidėliotina informacija apsinuodijus +370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and **Emergency Department**

Material name: SC-90 - Action Can - UK

2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Netherlands National Poisons Information

Center (NVIC)

030-274 88 88 (Only for the purpose of informing medical personnel in cases of

acute intoxications)

Norway Norwegian Poison

Information Center

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Romania Biroul RSI si Informare Toxicologica $021.318.36.06 \ (Available\ 8:00AM-3:00PM.\ SDS/Product\ information\ may\ not\ be$

available for the Emergency Service.)

Slovakia National Toxicological Information

Centre

+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Sweden National Poison Information Center

112 - and ask for Poison Information (Available 24 hours a day. SDS/Product

information may not be available for the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols Category 3 H229 - Pressurized container: May

burst if heated.

Health hazards

Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Hazard summary Aerosol CONTENTS UNDER PRESSURE.

Pressurised container may explode when exposed to heat or flame. Causes serious eye irritation.

Occupational exposure to the substance or mixture may cause adverse health effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Decyl alcohol, ethoxylated

Hazard pictograms



Signal word Warning

Hazard statements

H229 Pressurized container: May burst if heated.

H319 Causes serious eye irritation.

Precautionary statements

Prevention

P102 Keep out of reach of children.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P251 Do not pierce or burn, even after use. P280 Wear eye protection/face protection.

Response Not assigned.

Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Not assigned.

Supplemental label information EUH208 - Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE;1,2-BENZISOTHIAZOLIN-3-ONE. May

produce an allergic reaction.

26% by mass of the contents are flammable. Regulation (EC) No 648/2004 on detergents:

aliphatic hydrocarbons 15-30% non-ionic surfactants <5%

2.3. Other hazards This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or

Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Material name: SC-90 - Action Can - UK

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	10 - 25	EC926-141-6 -	01-2119456620-43	-	
Classification	: Asp. Tox.	1;H304			
Decyl alcohol, ethoxylated	0 - 2,5	26183-52-8 500-046-6	-	-	
Classification	: Acute Tox.	4;H302;(ATE: 500 m	g/kg), Eye Dam. 1;H318		Α
1,2-BENZISOTHIAZOL-3(2H)-ONE;1 2-BENZISOTHIAZOLIN-3-ONE	, 0 - 0,05	2634-33-5 220-120-9	01-2120761540-60	613-088-00-6	
Classification	Skin Irrit. 2		g/kg), Acute Tox. 2;H330;(A 318, Skin Sens. 1;H317, Ad		
Specific Concentration Limits	: Skin Sens.	1;H317: C >= 0.05 %	, D		

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Note A: Not registered due to polymer status (no longer polymer list - directive 92/32/EEC).

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth. Do

not induce vomiting without advice from poison control center. If vomiting occurs, keep head low

so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and

delayed

Ingestion

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Will burn if involved in a fire.

5.1. Extinguishing media

Suitable extinguishing

Foam. Dry chemicals. Carbon dioxide (CO2).

media

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fightingProcedures
Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapour pressure build up.

Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Keep unnecessary personnel away. Ensure adequate ventilation, Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in

Section 8 of the SDS.

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up Avoid discharge into drains, water courses or onto the ground.

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. This product is miscible in water. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene

7.2. Conditions for safe storage, including any incompatibilities

Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame. heat or other sources of ignition. Store away from incompatible materials (see Section 10 of the

Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Austria

Occupational exposure limits

Components	Type	Value	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA (MAK)	200 ppm	
Belgium. Exposure Limit Values			
Components	Туре	Value	Form
White mineral oil (CAS 8042-47-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Bulgaria. OELs. Regulation No 13 on Components	protection of workers agains Type	t risks of exposure to che Value	mical agents at work
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	
Czech Republic. OELs. Government D	ecree 361		
Components	Туре	Value	Form
White mineral oil (CAS 8042-47-5)	Ceiling	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol
Denmark. Exposure Limit Values			
Components	Туре	Value	Form
White mineral oil (CAS 8042-47-5)	TLV	1 mg/m3	Mist.

Material name: SC-90 - Action Can - UK

•			
Germany Components	Туре	Value	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	300 mg/m3	
Germany. DFG MAK List (advisory OELs) in the Work Area (DFG)	. Commission for the Investigation	of Health Hazards	of Chemical Compounds
Components	Туре	Value	Form
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Respirable fraction.
Germany. TRGS 900, Limit Values in the A	Ambient Air at the Workplace Type	Value	Form
White mineral oil (CAS 8042-47-5)	AGW	5 mg/m3	Respirable fraction.
Greece. OELs (Decree No. 90/1999, as am	ended)		
Components	Туре	Value	Form
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Mist.
Hungary. OELs. Joint Decree on Chemica Components	l Safety of Workplaces Type	Value	
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	
Iceland. OELs. Regulation 154/1999 on oc Components	cupational exposure limits Type	Value	Form
White mineral oil (CAS 8042-47-5)	TWA	1 mg/m3	Mist.
Ireland. Occupational Exposure Limits			_
Components	Туре	Value	Form
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.
Italy. Occupational Exposure Limits	T	Walne	Farm
Components	Type	Value	Form
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.
Lithuania. OELs. Limit Values for Chemic Components	cal Substances, General Requireme Type	ents Value	Form
White mineral oil (CAS 8042-47-5)	STEL	3 mg/m3	Fume and mist.
0012 11 0)	TWA	1 mg/m3	Fume and mist.
Netherlands Components	Туре	Value	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA (MAC)	1200 mg/m3	
Netherlands. OELs (binding) Components	Туре	Value	Form
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Mist.
Norway. Administrative Norms for Contar Components	ninants in the Workplace Type	Value	Form

Material name: SC-90 - Action Can - UK

White mineral oil (CAS 8042-47-5)

BDS002570AE Version #: 01 Issue date: 27-May-2021 5 /

1 mg/m3

Mist.

TLV

Components	Туре	Value	Form
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.
Portugal. VLEs. Norm on occupa Components	tional exposure to chemical agent Type	s (NP 1796) Value	Form
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.
Romania. OELs. Protection of wo Components	rkers from exposure to chemical Type	agents at the workplace Value	
White mineral oil (CAS 8042-47-5)	STEL	10 mg/m3	
	TWA	5 mg/m3	
Slovakia. OELs. Regulation No. 3 Components	00/2007 concerning protection of Type	health in work with chem Value	nical agents Form
White mineral oil (CAS 8042-47-5)	STEL	3 mg/m3	Fume and mist.
		15 ppm	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
		5 ppm	Fume and mist.
	cerning protection of workers aga	inst risks due to exposu	re to chemicals while worki
(Official Gazette of the Republic of Components	of Slovenia) Type	Value	Form
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Respirable fraction.
Spain. Occupational Exposure Li Components	mits Type	Value	Form
White mineral oil (CAS 8042-47-5)	STEL	10 mg/m3	Mist.
· · · · · · · · · · · · · · · · · · ·	TWA	5 mg/m3	Mist.
	nt Authority (AV), Occupational Ex		
Components	Туре	Value	Form
White mineral oil (CAS 8042-47-5)	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
Switzerland. SUVA Grenzwerte au Components	m Arbeitsplatz Type	Value	Form
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.
•	biological exposure limits noted for t	he ingredient(s).	
•	ow standard monitoring procedures.	3 ()	
cedures			
•			
cedures			
cedures ived no effect levels (DNELs) <u>General Population</u> Components	Value	Assessment factor	Notes
cedures ived no effect levels (DNELs) General Population Components 1,2-BENZISOTHIAZOL-3(2H)-ONE	;1,2-BENZISOTHIAZOLIN-3-ONE (0	CAS 2634-33-5)	
cedures ived no effect levels (DNELs) General Population Components 1,2-BENZISOTHIAZOL-3(2H)-ONE Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	;1,2-BENZISOTHIAZOLIN-3-ONE (0 0,345 mg/kg bw/day		Notes Repeated dose toxicity Repeated dose toxicity
ived no effect levels (DNELs) General Population Components 1,2-BENZISOTHIAZOL-3(2H)-ONE Long-term, Systemic, Dermal Long-term, Systemic, Inhalation White mineral oil (CAS 8042-47-5)	;1,2-BENZISOTHIAZOLIN-3-ONE (0 0,345 mg/kg bw/day n 1,2 mg/m3	CAS 2634-33-5) 200	Repeated dose toxicity
cedures ived no effect levels (DNELs) General Population Components 1,2-BENZISOTHIAZOL-3(2H)-ONE Long-term, Systemic, Dermal Long-term, Systemic, Inhalation White mineral oil (CAS 8042-47-5) Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	;1,2-BENZISOTHIAZOLIN-3-ONE (0 0,345 mg/kg bw/day n 1,2 mg/m3 93 mg/kg bw/day	CAS 2634-33-5) 200	Repeated dose toxicity
cedures ived no effect levels (DNELs) General Population Components 1,2-BENZISOTHIAZOL-3(2H)-ONE Long-term, Systemic, Dermal Long-term, Systemic, Inhalation White mineral oil (CAS 8042-47-5) Long-term, Systemic, Dermal Long-term, Systemic, Inhalation Workers	;1,2-BENZISOTHIAZOLIN-3-ONE (0 0,345 mg/kg bw/day n 1,2 mg/m3 93 mg/kg bw/day n 35 mg/m3	CAS 2634-33-5) 200 50	Repeated dose toxicity Repeated dose toxicity
cedures ived no effect levels (DNELs) General Population Components 1,2-BENZISOTHIAZOL-3(2H)-ONE Long-term, Systemic, Dermal Long-term, Systemic, Inhalation White mineral oil (CAS 8042-47-5) Long-term, Systemic, Dermal Long-term, Systemic, Inhalation Workers Components	;1,2-BENZISOTHIAZOLIN-3-ONE (0 0,345 mg/kg bw/day n 1,2 mg/m3 93 mg/kg bw/day	CAS 2634-33-5) 200 50 Assessment factor	Repeated dose toxicity

Material name: SC-90 - Action Can - UK

SDS EU

25 6,81 mg/m3 Repeated dose toxicity Long-term, Systemic, Inhalation

White mineral oil (CAS 8042-47-5)

220 mg/kg bw/day Long-term, Systemic, Dermal Long-term, Systemic, Inhalation 160 mg/m3

Predicted no effect concentrations (PNECs)

Components Value **Assessment factor** Notes White mineral oil (CAS 8042-47-5) 300 Secondary poisoning 17 g/kg Oral

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Use personal protective equipment as required. Personal protection equipment should be chosen **General information**

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

Skin protection

- Hand protection When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough

time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Neoprene gloves are

recommended. Suitable gloves can be recommended by the glove supplier.

- Other

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with

organic vapour cartridge. (Filter type ABEK)

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

When using do not smoke. Always observe good personal hygiene measures, such as washing Hygiene measures

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to

acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid. Aerosol Form Colour White

Characteristic odor. Odour

-182 °C (-295,6 °F) estimated Melting point/freezing point

Boiling point or initial boiling

point and boiling range

Not available.

Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

Not available.

(%)

> 100,0 °C (> 212,0 °F) Flash point > 200 °C (> 392 °F) **Auto-ignition temperature Decomposition temperature** Not available.

9.8

pН

Material name: SC-90 - Action Can - UK

Solubility(ies)

Soluble in water Solubility (water) 3000 hPa estimated Vapour pressure Vapour density Not available.

Relative density 0,96 g/cm3

Relative density temperature 20 °C (68 °F)

Particle characteristics Not available.

9.2 Other safety characteristics

Aerosol spray enclosed space

Deflagration density > 300 s/m³ **Aerosol spray ignition** < 15 cm

distance

Chemical family Cleaner

Explosive properties

Not applicable.

Not explosive.

Heat of combustion (NFPA

30B)

3,24 kJ/g estimated

Oxidising properties Not oxidising.

VOC 152 g/l

SECTION 10: Stability and reactivity

10.1. ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid high temperatures.10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous Carbon oxides.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation

may be harmful.

Skin contact May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

11.1. Information on toxicological effects

Acute toxicity Classification based on calculation method. Based on available data, the classification criteria are

not met.

Product Species Test Results

SC-90

Acute

Dermal

LD50 Rabbit 5677 mg/kg

Inhalation

LC50 Rat 13528 mg/m3, 8 h

Oral

LD50 Rat 7827 mg/kg

Components Species Test Results

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

<u>Acute</u>

Dermal

LD50 Rabbit > 5000 mg/kg

Inhalation

LC50 Rat > 5000 mg/m3, 8 h

Material name: SC-90 - Action Can - UK

Components **Species Test Results**

Oral

LD50 Rat > 5000 mg/kg

Based on available data, the classification criteria are not met. Skin corrosion/irritation

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitisation Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Skin sensitisation Germ cell mutagenicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Carcinogenicity

Hungary, 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

Specific target organ toxicity -

single exposure

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Not likely, due to the form of the product.

Mixture versus substance

information

Not available.

11.2. Information on other hazards

Endocrine disrupting

properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

Other information May cause allergic respiratory and skin reactions.

SECTION 12: Ecological information

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results**

1,2-BENZISOTHIAZOL-3(2H)-ONE;1,2-BENZISOTHIAZOLIN-3-ONE (CAS 2634-33-5)

Aquatic

Acute

Crustacea LC50 Harpacticoid copepod (Nitocra spinipes) 21 - 30 mg/l, 96 hours Fish LC50 Bleak (Alburnus alburnus) 8 - 13 mg/l, 96 hours

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Aquatic

Acute

LC50 Algae Algae 1000 mg/l, 72 h Crustacea EC50 Daphnia 1000 mg/l, 48 h LC50 1000 mg/l, 96 h Fish Oncorhynchus mykiss

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient

Not available.

n-octanol/water (log Kow)

Not available. No data available.

12.4. Mobility in soil

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.5. Results of PBT and vPvB

Bioconcentration factor (BCF)

assessment

None known

12.6. Endocrine disrupting properties 12.7. Other adverse effects

The product contains volatile organic compounds which have a photochemical ozone creation

potential.

12.8. Additional information

Estonia Dangerous substances in soil Data

1,2-BENZISOTHIAZOL-3(2H)-ONE;1,2-BENZISOTHIAZ

OLIN-3-ONE (CAS 2634-33-5)

Chemical pesticides (As the total sum of the active substances) 0.5 mg/kg

Chemical pesticides (As the total sum of the active substances) 20

mg/kg

Chemical pesticides (As the total sum of the active substances) 5

mg/kg

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents Disposal methods/information

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Special precautions

SECTION 14: Transport information

ADR

UN1950 14.1. UN number

14.2. UN proper shipping

AEROSOLS

14.3. Transport hazard class(es)

Class 2.2 Subsidiary risk

Not available. Hazard No. (ADR)

Tunnel restriction code (E) ADR/RID - Classification 5A

code:

14.4. Packing group Not applicable

14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

UN1950 14.1. UN number **AEROSOLS** 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

Class 2.2 Subsidiary risk

Not applicable 14.4. Packing group

14.5. Environmental hazards No

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

IMDG

UN1950 14.1. UN number 14.2. UN proper shipping **AEROSOLS**

name

14.3. Transport hazard class(es)

2.2 Subsidiary risk

Not applicable 14.4. Packing group

14.5. Environmental hazards Marine pollutant

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

14.7. Maritime transport in bulk Not established.

according to IMO instruments

ADR; IATA; IMDG



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **EU regulations**

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

1,2-BENZISOTHIAZOL-3(2H)-ONE;1,2-BENZISOTHIAZOLIN-3-ONE (CAS 2634-33-5)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

Material name: SC-90 - Action Can - UK BDS002570AE Version #: 01 Issue date: 27-May-2021

National regulations

This safety data sheet conforms to the following laws, regulations and standards:

Act on the management of packaging and packaging waste of June 13, 2013

Regulation of the Minister of Health of June 11, 2012 on the categories of dangerous substances and dangerous preparations whose packaging should be fitted with child-resistant closures and a tactile warning of danger

REGULATION OF THE MINISTER OF HEALTH of February 2, 2011 on tests and measurements of factors harmful to health in working environments

Regulation of Ministry of Labor and Social Policy of June 6, 2014. On the matter of maximum permissible concentrations and intensities of harmful factors in the work environment (Journal of Laws 2014, item. 817)

Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices Decree No. 25/2000. (IX. 30.) EüM-SzCsM of the Minister of Health and the Minister of Social and Family Affairs on chemical safety at work Act No. 93 of 1993 on Labour Safety (1993.évi XCIII.), as amended

Government Decree No. 220 of 2004 (VII. 21.) providing rules on the protection of surface waters quality

Government Decree No. 98/2001 (VI. 15.), on the conditions of the activities related to hazardous waste, and Ministry of Environmental Affairs Decree No. 16/2001 (VII. 18.), on the register of waste s Public Act No. XXV of 2000 on Chemical Safety, and Application Decree No. 44/2000. (XII.27.) EüM [of the Ministry of Health]

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value.

CEN: European Committee for Standardization.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit.

TLV: Threshold Limit Value.

TWA: Time Weighted Average.

VLE: Exposure Limit Value.

VME: Exposure Average Value. VOC: Volatile organic compounds.

vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

References

Information on evaluation method leading to the classification of mixture

Full text of any H-statements not written out in full under Sections 2 to 15 Not available.

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

Material name: SC-90 - Action Can - UK

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Revision information

Training information

Follow training instructions when handling this material.

Disclaimer

CRC Industries Europe UK Limited cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Material name: SC-90 - Action Can - UK