

SDS ATTACHMENT

PLEASE ATTACH THIS COMPLETED SHEET TO THE SDS FOR:

PRODUCT:

TF90 Fast Drying Solvent Cleaner

DATE:

(SDS date)

17-Nov-22

1. Manufacturer/Supplier:

Tradegear Ltd
Level 1, 99 Clarence Street
Riccarton
Christchurch 8011
New Zealand
Phone: 0800 22 44 34 or +64 3 341 8055
Fax: 0800 22 11 51 or +64 9 522 8833
24 hr emergency contact: +64 21 510 622
Website: www.tradegear.co.nz
Email: office@tradegear.co.nz

Emergency Information:

National Poison Centre:

0800 764 766

2 & 15. Hazards Identification & Regulatory Requirements:

Product Name:	TF-90 Aerosol
Group Standard, Approval #	Aerosols (Flammable) Group Standard 2006, HSR002515
HSNO Classes (from GHS codes)	2.1.2A, 6.1E, 6.3B, 6.4A, 9.1C
Class 9 Hazard/Precautionary Statements	DANGER Extremely flammable aerosol. May be harmful if swallowed. Causes mild skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects. Avoid release into the environment. Pressurised container: do not pierce or burn, even after use. Read label and safety data sheet before use. Keep out of reach of children. If medical advice is needed, have the product container or label at hand. Beware: deliberately sniffing or inhaling concentrated contents can
TEL or EEL applicable?	None

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Trade name or designation of the mixture	TF-90
Registration number	-
Synonyms	None.
Product code	UDS000737AE
Issue date	17-November-2022
Version number	1.0
Revision date	17-November-2022

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Cleaners - Heavy duty
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Company name	CRC Industries UK Ltd.
Address	Wylds Road Castlefield Industrial Estate TA6 4DD Bridgwater Somerset United Kingdom
Telephone	+44 1278 727200
Fax	+44 1278 425644
E-mail	hse.uk@crcind.com
Website	www.crcind.com

Company name	CRC Industries Europe bv
Address	Touwslagerstraat 1 9240 Zele Belgium
Telephone	+32(0)52/45.60.11
Fax	+32(0)52/45.00.34
E-mail	hse@crcind.com
Website	www.crcind.com

1.4. Emergency telephone number Tel.:(+44)(0)1278 72 7200 (office hours: 9-17h GMT)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture**

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended**Physical hazards**

Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
----------	------------	---

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.

Environmental hazardsHazardous to the aquatic environment,
long-term aquatic hazard

Category 2

H411 - Toxic to aquatic life with
long lasting effects.**2.2. Label elements****Label according to Regulation (EC) No. 1272/2008 as amended****Contains:** Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic, Propan-2-ol; Isopropyl alcohol; Isopropanol**Hazard pictograms****Signal word**

Danger

Hazard statements

H222 Extremely flammable aerosol.
 H229 Pressurized container: May burst if heated.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements**Prevention**

P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing mist/vapours.
 P271 Use only outdoors or in a well-ventilated area.

Response

Not assigned.

Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None.**2.3. Other hazards**

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic	30 - 60	- 927-510-4	01-2119475515-33	649-328-00-1	
Classification: Flam. Liq. 2;H225, Skin Irrit. 2;H315, STOT SE 3;H336, Asp. Tox. 1;H304, Aquatic Chronic 2;H411					
Propan-2-ol; Isopropyl alcohol; Isopropanol	10 - 20	67-63-0 200-661-7	01-2119457558-25	603-117-00-0	#
Classification: Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336					

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).
 M: M-factor
 PBT: persistent, bioaccumulative and toxic substance.
 vPvB: very persistent and very bioaccumulative substance.
 All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures**General information**

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.
4.2. Most important symptoms and effects, both acute and delayed	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards	Extremely flammable aerosol.
5.1. Extinguishing media	
Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Special fire fighting procedures	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.
For emergency responders	Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
6.2. Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
---	---

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1250 mg/m ³
		500 ppm
	TWA	999 mg/m ³ 400 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

General population

Components	Value	Assessment factor	Notes
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)			
Long-term, Systemic, Dermal	319 mg/kg bw/day	2	Repeated dose toxicity
Long-term, Systemic, Inhalation	89 mg/m ³	2	Repeated dose toxicity
Long-term, Systemic, Oral	26 mg/kg bw/day	2	Repeated dose toxicity

Workers

Components	Value	Assessment factor	Notes
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)			
Long-term, Systemic, Dermal	888 mg/kg bw/day	1	
Long-term, Systemic, Inhalation	500 mg/m ³	1	

Predicted no effect concentrations (PNECs)

Components	Value	Assessment factor	Notes
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)			
Freshwater	140.9 mg/l	1	
Secondary poisoning	160 mg/kg	30	Oral
Sediment (freshwater)	552 mg/kg		
Soil	28 mg/kg		

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection

Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

Skin protection

- Hand protection

When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended. Suitable gloves can be recommended by the glove supplier.

- Other

Wear appropriate chemical resistant clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge and full facepiece. (Filter type A)

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

Hygiene measures	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol.
Colour	Colourless.
Odour	Characteristic odor.
Odour threshold	Not available.
pH	Not applicable.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	82 °C (179.6 °F)
Flash point	-4.0 °C (24.8 °F) Closed cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	1.1 %
Explosive limit – upper (%)	7 %
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0.73 g/cm ³
Solubility(ies)	
Solubility (water)	Insoluble in water
Auto-ignition temperature	> 200 °C (> 392 °F)
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
9.2. Other information	No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Acids. Strong oxidising agents. Chlorine. Isocyanates.
10.6. Hazardous decomposition products	Carbon oxides.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.

Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components	Species	Test Results
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic		
Acute		
Dermal		
LD50	Rat	2920 mg/kg
Inhalation		
LC50	Rat	23.3 mg/l
Oral		
LD50	Rat	5840 mg/kg

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Acute		
Inhalation		
LC50	Rat	> 25000 mg/m3, 6 h

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory sensitisation Based on available data, the classification criteria are not met.

Skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Not an aspiration hazard.

Mixture versus substance information Not available.

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic		
Aquatic		
<i>Acute</i>		
Crustacea	EC50 Daphnia	3 mg/l, 48 hours
Fish	LC50 Fish	> 13.4 mg/l, 96 hours
<i>Chronic</i>		
Crustacea	NOEC Daphnia	0.17 mg/l, 21 days

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Aquatic		
<i>Acute</i>		
Crustacea	LC50 Brine shrimp (Artemia salina)	> 10000 mg/l, 24 hours
Fish	LC50 Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours

12.2. Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient**n-octanol/water (log Kow)**

Propan-2-ol; Isopropyl alcohol; Isopropanol 0.05

Bioconcentration factor (BCF) Not available.**12.4. Mobility in soil** No data available.**12.5. Results of PBT and vPvB assessment** This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.**12.6. Other adverse effects** The product contains volatile organic compounds which have a photochemical ozone creation potential.
GWP: 1**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Residual waste** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.**EU waste code** The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.**Disposal methods/information** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.**Special precautions** Dispose in accordance with all applicable regulations.**SECTION 14: Transport information****ADR****14.1. UN number** UN1950**14.2. UN proper shipping name** AEROSOLS, flammable**14.3. Transport hazard class(es)****Class** 2.1**Subsidiary risk** -**Label(s)** 2.1**Hazard No. (ADR)** Not assigned.**Tunnel restriction code** D**ADR/RID - Classification** 5F**code:****14.4. Packing group** Not assigned.**14.5. Environmental hazards** Yes**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**RID****14.1. UN number** UN1950**14.2. UN proper shipping name** AEROSOLS, flammable**14.3. Transport hazard class(es)****Class** 2.1**Subsidiary risk** -**Label(s)** 2.1**14.4. Packing group** Not assigned.**14.5. Environmental hazards** Yes**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**ADN****14.1. UN number** UN1950**14.2. UN proper shipping name** AEROSOLS, flammable**14.3. Transport hazard class(es)****Class** 2.1**Subsidiary risk** -**Label(s)** 2.1

- 14.4. Packing group Not assigned.
- 14.5. Environmental hazards Yes
- 14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

- 14.1. UN number UN1950
- 14.2. UN proper shipping name Aerosols, flammable
- 14.3. Transport hazard class(es)
 - Class 2.1
 - Subsidiary risk -
- 14.4. Packing group Not assigned.
- 14.5. Environmental hazards Yes
- ERG Code 10L
- 14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
- Other information
 - Passenger and cargo aircraft Allowed with restrictions.
 - Cargo aircraft only Allowed with restrictions.

IMDG


- 14.1. UN number UN1950
- 14.2. UN proper shipping name Aerosols, flammable, MARINE POLLUTANT
- 14.3. Transport hazard class(es)
 - Class 2.1
 - Subsidiary risk -
- 14.4. Packing group Not assigned.
- 14.5. Environmental hazards
 - Marine pollutant Yes
- EmS F-D, S-U
- 14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

- 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

ADN; ADR; IATA; IMDG; RID



Marine pollutant



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Other regulations

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value.

CEN: European Committee for Standardization.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit.

TLV: Threshold Limit Value.

TWA: Time Weighted Average.

VOC: Volatile organic compounds.

vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Revision information

None.

Training information

Follow training instructions when handling this material.

Disclaimer

CRC Industries Europe UK Limited cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.