

# TECHNICAL DATA SHEET

Tradegear | FOR THE TRADE

Tradegear Ltd  
Telephone: 027 510 8898  
Email: Office@tradegear.co.nz  
Web: www.tradegear.co.nz

## Tradegear Premium Marking Spray



Tradegear Premium Marking Spray is a premium marking out paint designed for a range of applications including: construction, landscaping, civil works and surveying.

Tradegear Premium Marking Spray is suitable for use with the Long Arm Handle (also available from Tradegear) and the 2 Wheel Spot Marking Handle.

### DIRECTIONS FOR USE

**SHAKE, SHAKE, SHAKE!** Performance is improved with shaking before and during use.  
The more you shake, the better it sprays.

#### Suitable Surfaces

Concrete, bitumen, steel and timber.

#### Ideal Application Temperature

Between 5°C and 40°C. Avoid use in windy conditions.

#### Before Use

Refer to Technical Data Sheet and Safety Data Sheet before use.

#### Application

Before spraying, shake can for at least 45 seconds AFTER the mixing ball begins to rattle in order to reconstitute propellant, solvent and paint. Shake can occasionally during use. Hold the can in the INVERTED position (upside down), approximately 10-15cm from the surface. Spray width can be adjusted by moving closer or further from the surface to be sprayed.

#### Drying Time

Touch dry in 5 minutes (25°C).

Drying will be slower in cold and humid conditions, in the absence of ventilation or where heavy film build is applied.

#### After Spraying

Prevent blocking by holding the can UPRIGHT and spraying until only clear gas escapes. Also wipe spray tip of nozzle clean. Clean up wet paint with acetone or general purpose thinner.

### TECHNICAL DATA

Size:	350g Aerosol
Finish:	Matte
Colour:	8 Standard and 6 Fluoro colours
Consistency:	Liquid
VOC:	<450g/L
Coverage:	Will produce 200+ 'X' marks, up to 120 linear meters (depending on surface and colour used).
Clean Up:	Acetone or General Purpose Thinner.

Tradegear Ltd  
Telephone: 027 510 8898  
Email: [Office@tradegear.co.nz](mailto:Office@tradegear.co.nz)  
Web: [www.tradegear.co.nz](http://www.tradegear.co.nz)

## STORAGE

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C. Store in a well-ventilated place. For longer term storage, it is recommended to store carton upright, to stop crucial gasses from expanding and/or escaping, which could cause an explosion. Shaking well will improve performance by reconstituting propellant, solvent and paint that may have settled in the bottom of the can.

Extremely flammable aerosol. May burst if heated. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources as well as machinery and/or vehicles.

Never leave aerosols inside a car, i.e. on dashboards and in boots or in any other enclosed vehicle. The internal temperature of the vehicle can be up to 30°C hotter than the outside temperature.

If an aerosol is kept near a heat source, the pressure in the can increases rapidly to levels that exceed the can

## DISPOSAL

Pressurised container: Do not pierce or burn, even after use. Aerosol should be completely emptied prior to disposal. Dispose of contents/container accordingly to regional regulations.

## FIRST AID/SECURITY INFORMATION

Please refer to Safety Data Sheet before use. Safety Data Sheets are available for download from our website: [www.tradegear.co.nz](http://www.tradegear.co.nz).

Call a POISON CENTRE: New Zealand: 0800 764 766 or a doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

## DISCLAIMER

The information provided within the Technical Data Sheet is intended as a guide only. The slip resistance and performance of this product depends on many factors outside the control of Tradegear; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Tradegear recommends consumers undertake their own risk assessment prior to use to determine the suitability of the product for the particular use intended. Some factors to consider:

- Slip resistance required
- Surface type
- Volume of traffic
- Potential exposure to any surface contaminants eg. water, solvents or chemicals.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact Tradegear on 027 510 8898 or 0800 22 44 34

**The more you shake, the better it sprays.**