

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



Dy-Mark RUST REFORMER



Dy-Mark Rust Reformer chemically converts rust on metal surfaces and protects against further corrosion. **Rust Reformer** dries to a flat black finish within 40 minutes and can be sanded after 3 hours. With minimal surface preparation required, **Rust Reformer** is ideal for use on industrial equipment, fences, railings and metal furniture.

DIRECTIONS FOR USE

Suitable Surfaces:

All rusty metal surfaces such as steel and iron. Not recommended for galvanised iron.

Ideal Application Temperature:

Between 10°C and 40°C. Avoid use in windy conditions.

Preparation:

Remove all loose paint and rust with a wire brush, sand paper or mechanical sander. Degrease and wash the surface with suitable cleaner. Rinse thoroughly and allow to dry.

Application:

Before spraying, cover surrounding areas to protect from overspray. **Shake can** at least 45 seconds **AFTER** the mixing ball begins to rattle. Shake can occasionally during use. Hold can upright approximately 20-25cm from surface. Spray with a smooth sweeping motion. To prevent paint from sagging, apply several light mist coats rather than one heavy coat. **Adjust nozzle** to achieve desired spray pattern. Use horizontal setting to spray up and down and the vertical setting to spray across.

Coverage:

Approximately 2m² per can (depending on the surface and amount of overspray).

Drying Time:

Touch dry in 30-40 minutes (25°C).

Coated surface can be sanded after 3 hours.

Drying time will be slower in cold and humid conditions, in the absence of ventilation or where heavy film build is applied.

Drying Time:

Prevent blocking by holding the can upside down and spraying until only clear gas escapes. Also **wipe spray tip** of nozzle clean. **Clean up** wet paint with **Dy-Mark Xylene Specialty Thinner** or **General Purpose Thinner**.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



TECHNICAL DATA

Size:	350g Aerosol
Colour:	Black
Finish:	Matt
Consistency:	Liquid
Propellant:	Dimethyl ether

STORAGE

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in well-ventilated place.

DISPOSAL

Dispose of contents/container according to regional regulations.

FIRST AID / SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website www.dymark.com.au or from the following QR code:



Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use, to determine the suitability of the product for the particular use intended.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.